

PERFORMANCE DECLARATION

(Regulation UE nr.305/2011 – annexe III)
Nr. 017_TFM05

①	Unique identification code of the product-type:	TFM05																														
②	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):	See label (serial number)																														
③	Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	Input/output devices 0 in – 5 out																														
④	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):	Tecnoalarm s.r.l. - Via Ciriè 38 10099 SAN MAURO (TO) - ITALY																														
⑤	Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	N.A.																														
⑥	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:	System 1																														
⑦	In case of the declaration of performance concerning a construction product covered by a harmonized standard: EVPU - the notified product certification body - shall issue the certificate of constancy of performance of the product on the basis of: (i) determination of the product-type on the basis of type testing (including sampling), type calculation, tabulated values or descriptive documentation of the product; (ii) initial inspection of the manufacturing plant and of factory production control; (iii) continuous surveillance, assessment and evaluation of factory production control;	EVPU – NB nr. 1293																														
⑧	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:	Not applicable																														
⑨	DECLARED PERFORMANCE																															
	Essential characteristics	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 15%; text-align: center;">Declared Performance</th> <th colspan="2" style="text-align: center;">Harmonized standard</th> </tr> <tr> <th></th> <th style="width: 35%; text-align: center;">EN54-18:2005/AC:2007</th> <th style="width: 35%; text-align: center;">EN54-17:2005</th> </tr> <tr> <td>Response delay (response time)</td> <td style="text-align: center;">Pass</td> <td style="text-align: center;">Art. 5.2</td> </tr> <tr> <td>Performance under fire conditions</td> <td style="text-align: center;">Pass</td> <td style="text-align: center;">Art. 5.1.4</td> </tr> <tr> <td>Operational reliability</td> <td style="text-align: center;">Pass</td> <td style="text-align: center;">Art. 5.1.4</td> </tr> <tr> <td>Durability of operational reliability; temperature resistance</td> <td style="text-align: center;">Pass</td> <td style="text-align: center;">Art. 5.3-5.4</td> </tr> <tr> <td>Durability of operational reliability; vibration resistance</td> <td style="text-align: center;">Pass</td> <td style="text-align: center;">Art. 5.8 to 5.11</td> </tr> <tr> <td>Durability of operational reliability; humidity resistance</td> <td style="text-align: center;">Pass</td> <td style="text-align: center;">Art. 5.5-5.6</td> </tr> <tr> <td>Durability of operational reliability; corrosion resistance</td> <td style="text-align: center;">Pass</td> <td style="text-align: center;">Art. 5.7</td> </tr> <tr> <td>Durability of operational reliability; electrical stability</td> <td style="text-align: center;">Pass</td> <td style="text-align: center;">Art. 5.2-5.12</td> </tr> </table>	Declared Performance	Harmonized standard			EN54-18:2005/AC:2007	EN54-17:2005	Response delay (response time)	Pass	Art. 5.2	Performance under fire conditions	Pass	Art. 5.1.4	Operational reliability	Pass	Art. 5.1.4	Durability of operational reliability; temperature resistance	Pass	Art. 5.3-5.4	Durability of operational reliability; vibration resistance	Pass	Art. 5.8 to 5.11	Durability of operational reliability; humidity resistance	Pass	Art. 5.5-5.6	Durability of operational reliability; corrosion resistance	Pass	Art. 5.7	Durability of operational reliability; electrical stability	Pass	Art. 5.2-5.12
Declared Performance	Harmonized standard																															
	EN54-18:2005/AC:2007	EN54-17:2005																														
Response delay (response time)	Pass	Art. 5.2																														
Performance under fire conditions	Pass	Art. 5.1.4																														
Operational reliability	Pass	Art. 5.1.4																														
Durability of operational reliability; temperature resistance	Pass	Art. 5.3-5.4																														
Durability of operational reliability; vibration resistance	Pass	Art. 5.8 to 5.11																														
Durability of operational reliability; humidity resistance	Pass	Art. 5.5-5.6																														
Durability of operational reliability; corrosion resistance	Pass	Art. 5.7																														
Durability of operational reliability; electrical stability	Pass	Art. 5.2-5.12																														
The performance of the product identified in 1. and 2. is in conformity with the declared performance in 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in 4.																																

Signed for and on behalf of the manufacturer by:

Mr. Giovanni NEGRO - Management

San Mauro Torinese, April, 8, 2016

Signature

